

General data

FUEL

Diesel Diesel or Automotive Gas Oil (AGO) to EN 590

Petrol

Catalyst vehicles

- V8 high compression engines 95 RON unleaded to EN 228

- V8 low compression engines 91 RON unleaded to EN 228

Non-catalyst vehicles

- V8 low compression engines 95 RON leaded or 91 RON unleaded

WHEELS AND TYRES

Wheel and tyre size:

Steel wheels:

7J x 16 use with 215/75 R16 Pirelli Scorpion S/T 107T
use with 235/70 R16 Michelin XPC* 105H
use with 235/70 R16 Goodyear Wrangler HP 105H

Alloy wheels:

7J x 16 use with 235/70 R16 Goodyear Wrangler HP 105H
use with 235/70 R16 Michelin XPC* 105H
8J x 16 use with 255/65 R16 Goodyear Wrangler HP 109H
use with 255/65 R16 Michelin XPC* 109H
8J x 18 use with 255/55 R18 Goodyear Wrangler HP 109H

Road wheel nut torque 140 Nm

Tyre pressures:

All tyres (normal	Front:	1.9 bar
operating conditions)	Rear:	2.6 bar

All tyres (vehicle loaded	Front:	1.9 bar
to maximum gross	Rear:	3.2 bar
vehicle weight)		

NOTE: When towing, the additional load imposed may cause the tyre maximum load rating to be exceeded. This is permissible provided the load rating is not exceeded by more than 15% and that road speeds are limited to 100 km/h and tyre pressures are increased by at least 0.2 bar.