

GRANITE 1340 MAX

PACKED WITH MAX FEATURES PLUS 40" LONGER

ur Granite 1340 Max is MAXIMUM in every department! First, you get every single Granite feature. Then you get 40 l-on-g inches between centers...a 30% more milling capacity, and a heavy-duty motor with 30% more horsepower.

Because it's the Smithy Granite MAX, you get:

- 3-in-1 Lathe/Mill/Drill
- CNC-ready
- Dual Powerfeed
- · Industry-standard tooling

Because it's the 1340 MAX, you get.

- Industrial Tooling
- Same features as Granite Max 1324 but big 40" between centers
- Quick Change Gear Box
- Threading Dial
- Variable speed 2 HP motor
- X & Y Powerfeed (Lathe & Mill)
- Cuts right hand, left hand, metric & inch threads
- · Industrial standard tapers



GRANITE 1340 FEATURES:

• 3-in-1 Lathe/Mill/Drill

This is a multi-purpose metal working machine combining a lathe, a mill, and a drill. It provides a sturdy, accurate machine, in one compact versatile package.

• Industry-standard Tooling

R-8 Mill spindle, D1-4 Camlock Lathe Chuck, MT3 Tailstock, are all readily available standard tooling.

Positive Millhead Lock

For even greater stability and rigidity.

• Crash Protection System

Unique shear pin design protects your machine from major damage if the machine is ran past its limits of travel.



• Overload Protection

Safety shutoff prolongs motor life so that you can machine more projects.

• Easy Mount DRO & CNC Systems

Easier than ever to add computerization



Extended Millhead

Support larger workpieces for more efficient milling operations.



• 40% More Low-End Torque

Make heavier cuts without stalling your motor.



• 30% More Horsepower

Heavier cuts and smoother finishes.



• Tailstock, Now with 3" of Travel

Support long workpieces with the center securely place in the tailstock.



• Quick Change Gear Box

Cut your set-up time half. Select the feed rates and thread pitches with levers instead of change gears.





GRANITE 1340 MAX

GRANITE 1340 MAX FULL SPECIFICATIONS:

General Dimensions		Mill Specifications	
Length	62"	Column Diameter	3-3/16"
Width	22-1/2"	Dial Calibration Drill-Coarse Fee	d 0.05"
Height	39"	Dial Calibration Mill-Fine Feed	0.001"
Shipping Weight	910 lbs	Drawbars Size (included)	7/16"
Machine Weight	728 lbs	Drill Chuck Size (included)	5/8"
Crate Size	64-1/2" x 22-3/4" x 44"	Drill Chuck Arbor Size (included	R8/JT3
Footprint	64" x 36"	Feed Rates	.003020" (X-axis)
T-Slot Size	7/16"		.001006" (Y-axis)
Accuracy (TIR)	+/- 0.00078"	Head Rotation	360 Degrees
Powerfeed (X-Axis)	Yes	Head Travel	4-3/8"
Powerfeed (Y-Axis)	Yes	Quill Diameter	2-3/4"
Powerfeed (Z-Axis)	No	Quill Travel	4-7/8"
Table Size	6-3/4" x 17-3/4"	Spindle Center to Front of Chuck	8-1/2"
Threading Dial	Yes	Spindle Center to Lathe Spindle	
•		Spindle Center to Support Colum	_
Lathe Specifications		Spindle to Table Distance (Min-Max) 4" to 13-3/8"	
Distance Between Centers	40"	•	e (Range 0-2800 RPM)
Dial Calibration on Crossfeed	.001"	Spindle Taper	R8
Dial Calibration on Toolpost	.001"	Tool Size Limits	1"
Dial Calibration on Leadscrew	.001"	X-Axis Travel	9-1/2"
Dial Calibration on Longfeed R	ack .01"	Y-Axis Travel	7-5/8"
Dial Calibration on Tailstock .001"			•
Feed Rates	.003020" (X-axis)	Electrical	
	.001006" (Y-axis)	Amperage	15 Amps
Headstock Taper	MT4	Horsepower	2 HP
Lathe Chuck Bore	1.6"	Motor Type	D/C Variable Speed
Lathe Chuck Diameter	6"	Phase	Single
Lathe Chuck - Max. Diameter v	workpiece 6"	Voltage	110 Volts A/C
Lathe Chuck - Min. Diameter workpiece 1/8"		_	
Lathe Chuck Mount	D1-4 Camlock		
Lathe Chuck Type	3 Jaw Self Centering		
Spindle Bore	1.125"		
Spindle Speeds Varia	ble (Range 0-2800 RPM)		
Swing Over Bed	13"		
Swing Over Work Table	7-1/2"		
Tailstock Offset	19/32"		
Tailstock Taper	MT3		
Tailstock Barrel Travel	3"		
Threads-Inch	SAE 7-52 TPI		
Threads-Metric	0.35-6.5 mm		
Toolpost Travel	3-3/16"		
Tool Bit Size	1/2"		
X-Axis Travel (w/tailstock inst	alled) 20"		
Y-Axis Travel	7-5/8"	*Spe	cifications subject to change.



GRANITE 1340 MAX



Granite Tool Pak Includes:



Wrench Set	\$17.50	90 Degree Angle Vise	\$26.99
Drill Chuck & Arbor	Ψ17.00	End Mill Adapter (3/8")	\$18.50
(Millhead)	\$35.98	T-Slot Nut x2 (7/16")	\$3.98
Drill Chuck & Arbor	,	Drawbar Kit (7/16")	\$5.99
(Tailstock)	\$23.98	DVD	\$49.99
Dead Centers (MT3 & MT4)	\$18.98	Metric Threading	
6" 3-Jaw Chuck with Key	\$147.75	Change Gears	\$150.00
Safety Equipment	\$5.95		
Oil Can	\$6.00	Total	FREE \$541.76
Manual	\$6.50		
Carbide Bits	\$12.00		
End Mills (1/4", 3/8", 1/2"- with			
3/8" shank)	\$11.67		

Total Savings of \$1,141.76!

Shipping costs not included.

Machine Shipping is \$229.00 to the nearest CCX terminal.



For more information or for special offers Call TOLL FREE 1-800-476-4849