



Make	NISSAN
Model	Terrano II 2.7 Diesel Turbo (R20)
Engine	DT
Year	1993-

Application	Recommendation		Capacity (ltr)
Engine (DT)	Best	8100 Eco-nergy 5W-30 (g,h)	7.2
	Better	8100 X-clean C3 5W-30 (g,h)	
	Good	8100 X-cess 5W-40 (g,h)	
Manual Transmission	Best	MOTYLGEAR 75W-90 (v)	3.5
	Better	HD 80W-90 (v)	
Automatic Transmission			
Differential	Best	90 PA	2.8
	Better	GEAR COMPETITION 75W-140	
Coolant (30%)	INUGEL OPTIMAL		10
Transfer Box	Best	MOTYLGEAR 75W-90	2.3
	Better	HD 80W-90	
Mechanical steering	Best	MOTYLGEAR 75W-90	
	Better	HD 80W-90	
Brake & Clutch Fluid	Best	DOT 5.1 BRAKE FLUID	
	Better	DOT 4 BRAKE FLUID	
Multi-purpose grease	TOP GREASE 200		
Front Differential	Best	GEAR 300 75W-90	1.3
	Better	MOTYLGEAR 75W-90	
Power Steering	Best	DEXRON III	
	Better	DEXRON IID	
Auto-lock free running hubs (where fitted)	Nissan Part No. KPC 19-00025		
Hide Notes Oil Change Intervals			

Lubricant / Capacity Notes

- g. Diesel engine oil viscosity recommendations: below -30°C to -10°C, 5W-20; below -30°C to 15°C, 5W-30; -20°C to 20°C, 10W-30; -20°C to 30°C, 10W-40; -20°C to above 40°C, 10W-50, 15W-40, 15W-50; -10°C to above 40°C, 20W-40, 20W-50; -20°C to 0°C: 10W; -10°C to 20°C, 20W, 20W-20; 0°C to 30°C, 30; 20°C to above 40°C, 40, 50. (Turbo charged engines; 5W-30 not suitable, 5W-30 should only be used below 0°C)
- h. Additional engine oil quality recommendations: G4 may replace SG, D4 may replace CD and CE; Models 1999/2000 onward: petrol, SG/SH/SJ/SL/GF-1/GF-2/GF-3/A2 also suitable; diesel, CF-4/B1/B3 also suitable (never use CG-4)
- v. Alternative recommendations: <-30°C to 10°C, 75W; <-30°C to 30°C, 80W; <-30°C to 40°C, 75W-90; <-30°C to 40°C, 80W-90; -10°C to 30°C, 85W; 0°C to 40°C, 90; 10°C to >40°C, 140

General Notes

There are no notes to display for this model