

#### Radiator Spud Wrench, 1/2", five steps

- chrome vanadium steel
- in five different size:
- 3/8", 7/16", 1/2", 16 und 21 mm 1/2" drive







### Tap and Die Set, SAE and Metric combined

- especially for fine threads
- tungsten steel
- 2 tap holders2 die holders
- 1 T holder
- each 35 taps and dies in follwing sizes / flank leads: 6-32UNC 8-32UNC 4-40UNC 10-24UNC 12-24UNC 1/4-20UNC 10-32UNF 1/4-28UNF 1/4-24UNS 1/4-32UNS 5/16-18UNC 5/16-24UNF 3/8-16UNC 3/8-24UNF 7/16-14UNC 7/16-20UNF 1/2-13UNC 1/2-20UNF 9/16-12UNC 9/16-18UNF 3/4-10UNC 5/8-11UNC 3/4-16UNF 5/8-18UNF M6X1,0 M10X1,5 M8X1,25 M10X1,0 M11X1,5 M12X1,25 M12X1,75 M14X1,25 M18X1,5 1/8-27NP 1/4-18NPT









# **Heavy Duty Oil Filter Chain Wrench with Handle**

- heavy duty tool with duplex chain
- chain width approx. 22 mm
- handle satin chrome finished
- claw prevents slipping
- 180° swivel handle
- ease to use due to special chain-lock
- suitable for oil filters 60-160 mm
- length: 350 mm









#### **Professional Oil Filter Chain Wrench**

- pro version with duplex chain
- chain width 13 mm
- chain length 230 mm
- for every day workshop use
- also for stuck oil filters
- easy handling
- suitable for all steel filter cartridges with diameter 60-115 mm
- 1/2" drive











#### Oil and Fuel Filter Pliers with Swivel Jaws

- Jaws can be inclined up to 90° in both directions for easy removal of oil and fuel filters
- ideal for loosening filters in hard-to-raech areas that could not be loosened with common oil filter pliers
- jaws adjust in 4 positions every 30°
- can grip filters from 57 mm to 12 0mm
- slipping around the filters is avoided by 6 heavy claws on each jaw







#### **Renault Oilfilter Wrench**

- for Renault EF34 oil filters 76 mm 12-point
- stuck oil filters can be easily loosened due to extra long handle
- suitable for the following models:
- Renault Twingo R5, Rapid sedan with C, Clio, Kangoo petrol-R12 Espace III, Laguna sedan with F, Megan Kangoo with K Gasoline engines, R21 Espace I + III F Gasoline engines and Traffic with J gasoline engines
  - Ford Diesel 1.8 Motorcraft filter and EFL344
- Peugeot with Purflux Filter







## Protective Impact Socket Set, 1/2", 17, 19 and 21 mm

- chrome molybdenum steel
- length 85 mm
- suitable for manual and impact wrench use
- with plastic cover for perfect protection of aluminium rims
- with groove and hole
- colored plastic covers help to indicate the right size







## **Loosening Tool for Wheel Nut Covers**

- Wheel nut caps can be removed without damaging the rims
- especially suitable for aluminum rims
- gripping claws made of spring steelT-handle for easy working









#### Separating Knife and Bearing Puller Set

- facilitates disassembly of bearings
- opening size 45 mm to 60 mm
- M10 x 98 mm pressure spindle with 19 mm hex drive
- M10 x 58 mm pressure spindle with 19 mm hex drive
- spindle heads are equipped with a ball tip for removal of bearings



Item # 8277



#### Timing Tool Set for Fiat, Lancia, Alfa Romeo

- contains 1 special socket 1/2" dr. for disassembly of the phase adjuster
- 23 custom fit timing tools for inlet camshaft and exhaust camshaft prevent distortion of camshafts and allow setting them in mounting position for the tooth belt
- locking tools are numbered and have different colours to avoid mix-up
- can also be used for exact positioning of the crankshaft using the TDC setting plug and an optional micrometer (BGS 1938-1, not contained in set)
- fits following cars:
- Fiat Bravo 1,4 12V & 2,0 20V; Brava 1,4 12V & 2,0 20V Marea 2,0 20V; Coupe 1,8 16V; Barchetta 1,8 16V; Punto 1,8 16V
- Lancia K5 2,0 20V; 4 Zyl. VIS Motoren ab BJ. 96
   Delta 1,8 16V Step A; Dedra 1,8 16V Step A; Y10 1,4 12V
   Alfa 145 1400 &1600 16V Step A;
- Alfa 145 1400 &1600 16V Step A; Romeo 146 1400 &1600 16V Step A; 147 1600 16V Step A; 147 105 PS 147 1600 eco 103 hp; 155 1400 & 1600 16V Step A 156 1600 16V Step A; 156 1800 - 2000 16V 156 2000 JTS; 166 2000; GTV 2000 JTS Spider GT 2000 JTS 16V 165PS



Item # 8240



## **Camshaft Locking Tool**

- needed for tooth belt replacement and other engine timing jobs
- suitable for all Diesel and gasoline DOHC engines
- fixation by locking the camshafts against each other
- pins made of hardened steel for long tool life
- versatile applications because of 2 different arm lengths
- special knob on center arm can be turned into a place-saving position









### VAG 5 and 10 Cylinder Engine Locking Tool

- suitable for VW Phaeton and Touareg models as of 2003, Transporter as of 2004 with 5 and 10 cylinder Diesel engines - use like VW part Nr. T10193 / T10194
- for adjusting the camshaft when checking and repairing the engine
- no twisting of camshafts



Item # 8279



#### Pulley Holder for the High-Pressure Pump on Opel, Renault, Nissan

- suitable for Diesel engines with F9Q engine code in Opel, Renault, Nissan cars
- no need to disassemble the tooth belt
- pump wheel is locked securely because of high accuracy
- pump does not need to be re-adjusted
- helps to save time and money through reduced workload







## **Exhaust Pipe Separating Tool**

- for stuck-type hard to separate exhaust pipes
- suitable for pipe Ø 51mm-60mm
- solid steel jaws
- chrome plated screws for 17 mm & 3/8" drive
- 19 mm Zinc plated compression fitting
- compression range 0 mm -120 mm









## **Exhaust Pipe Rubber Ejection Pliers**

- facilitates removal of rubber hangers
- 25° opening angle for easy operation
- length: 285 mm









#### 5-piece Groove Nut Socket Set

- suitable for Mercedes differential, gear and rear axle flange
- for Mercedes series 107 114 115 116 126 ..
- allows gentle loosening and tightening using a torque wrench
- 1/2 drive

Item # 67220





#### **Pull and Press Sleeve Kit with 4 Spindles**

- universal type for all car models
- also for assembly or disassembly of silent bearings, rubber- and ball bearings
- also suitable for rubber bushes and rotary shaft seals
- smooth running because of high-quality ball bearing on spindle screw nut
- four 350 mm spindles in M10, M12, M14 und M16
- 20 inner pressure pad in 34, 36, 38 mm bis 72 mm 20 outer pressure pad in 44, 46, 48 mm bis 82 mm
- pressure pads are slotted for visual control



Item # 1514



#### 7-piece Drive Shaft Feeder Set

- for easy feeding of drive shaft into the wheel hub
- made of high grade steel
- based in a standardized industrial wheel bearing
- contains 6 spring bushings with different threads sizes
- can be used for following car types:

Subaru (M16X1.5)

VW Beetle, Touareg, Porsche Cayenne (M20X1.5) BMW E30, E46 (M22X1.5)

BMW E36, Mercedes W203 (M24X1.5) BMW E32, E34,E38,E39, X5 (M27X1.5) BMW E32, E34, E36 (M30X1.5)







## Nozzle Extractor, Four Tooth for MAN and Mercedes

- extractor made of carbon steel with four tooth counterholder and 27 mm 6-pt
- suitable for MAN and Mercedes trucks
- M14 Spindle
- spindle with 6mm hex drive for mounting nozzle on spindle
- allows easy and professional removal of the nozzle
- length: 105 mm









#### Valve Shim Remover for DOHC Engines

- suitable for all DOHC engines e.g. Volvo Opel, Ford, Renault ect.
- sliding t-bar for easy handling



Item # 8252



#### Special Crankshaft Rotation Tool for VAG 5 Cylinder Engines

- necessary for crankshaft adjustment
- suitable for all 5 cylinder VW Diesel engines e.g. in VW Touareg as of 2003 and Transporter as of 2004
- fixing screw allows easy mounting on crankshaft
- use like OEM VAG T10225







#### VW / Audi Engine Timing Tool Kit

- suitable for 1.8 L and 1.6L Turbo FSI engines
- crankshaft counterholder similar to OEM 3036 camshaft setting tool similar to OEM T10171
- counterholder for timing chain sprocket, camshaft, vibration damper similar OEM T10172
- adaptors for counterholder similar OEM T10172
- holder for chain adjuster for assembly and disassembly of the chain adjuster similar to OEM T20018 / 3366
- for following car models

#### Audi:

A3 1,8Turbo (AGN AGU AJQ APG APP AQA ARX ARY ARZ AUM AUQ) 1996-2003 A3 1,6FSI (BAG) 2003-2006

A3 1,8F31 (BAG) 2003-2006 S3 1,8Turbo (AMK APY BAM) 1996 A4 1,8Turbo (ADR AEB AJL AJP ANB APU AVJ AWT) 1994-2006 A6 1,8Turbo (ADR AEB AJL AJP ANB APU AVJ AWT) 1994-2006 Cabriolet 1,8 (ADR) 1997-2000

TT 1,8Turbo (AJQ APP APX AUM AUQ BAM) 1998-2006

Volkswagen:

Beetle 1,8Turbo (AVC) 1999-2006 Touran 1,6 FSI (BAG BLP) 2003-2007 Golf 1,8Turbo (AGN AGU AQA ARZ AUM AUQ) 1997-2005 Bora 1,8Turbo (AGN AGU AQA ARZ AUM AUQ) 1997-2005 Passat 1,8Turbo (ADR AEB ANB APT APU ARG AWT) 1996-2005

Seat:

Sharan 1,8Turbo (AJH AWC) 1997-2007 Ibiza 1,8Turbo (AQX AYP) 1999-2002 Cordoba 1,8Turbo (AQX AYP) 1999-2002 Leon 1,8Turbo (AQX AYP) 1999-2002 Leon 1,8Turbo (AQX AQN APG APP APT ARYAUQ) 1999-2005 Toledo Turbo (AQN APG APT ARYAUQ) 1999-2005 Alhambra 1,8Turbo (AJW AWC) 1997-2007

Skoda:

Octavia 1,8FSI Turbo (AGN AGU ARX ARZ AUM) 1996-2005 Octavia 1,8Turbo 20V RS (AUQ) 2000-2006 Oktavia 1,6FSI (BLF) 2004-2007

Item # 8261







#### **Double-Joint Pliers with Straight Tips**

- for hard to reach places such as behind interior trim, instrument panel, engine compartment, etc.
  - very small even when fully opened
- heavy duty 2-component plastic handle
- length 350 mm





#### **Double-Joint Pliers with Offset Tips**

- for hard to reach places such as behind interior trim, instrument panel, engine compartment, etc.
- very small even when fully opened
- heavy duty 2-component plastic handle
- length 350 mm





#### **Digital Toque Adaptors**

- allows you to use a ratchet like a torque wrench
- accuracy +/- 2%
- for right- and leftside operation





Item #	Description
979	Digital Toque Adaptor, 1/4", 6-30 Nm
978	Digital Toque Adaptor, 3/8", 27-135 Nm
977	Digital Toque Adaptor, 1/2", 40-200 Nm

## 300-piece Aluminum Seal Assortment

- especially suitable for oil drain plugs
- suitable for all popular vehicles

5x 9x1,0 8x14x1,5 12x16x1,0 14x20x1,5 18x24x1,5 22x29x1,5 6x10x1,0 9x14x1,0 12x16x1,5 14x20x2,0 20x24,5x1,5 24x29x1,5 6x12x1,0 10x14x1,0 12x18x1,5 16x20x1,5 20x24,5x0,8 24x32x2,0 8x12x1,0 10x14x1,5 13x18x1,0 16x22x1,5 19x26x2,0 26x34x2,0 8x14x1,0 10x16x1,0 14x18x1,5 18x22x1,5 22x27x1,0 28x36x2,0









## **Counter Sales Display**

- display made of 5 mm coated steel wire
  holder for ads
  height 230 mm, depth 185 mm, width 230 mm
  sold without tools



Item # 60



# Blank Key for Security Cylinder Locks Art. 8091-8094

- single blank key
  usually this key type is not available in stores.
  with this blank key every locksmith can copy a key for your cylinder lock





