



Technical Service Bulletin

19 Identifying and mixing factory fill engine coolants for review
19 22 28 2025303/13 January 28, 2022. Supersedes Technical Service Bulletin Group 19 number 22-27 dated January 10, 2022 for reasons listed below.

| Model(s) | Year | VIN Range | Vehicle-Specific Equipment |
|----------|-------------|-----------|----------------------------|
| All | 1994 – 2022 | All | Not Applicable |

Condition

| REVISION HISTORY | | |
|------------------|------------|--|
| Revision | Date | Purpose |
| 13 | - | Revised <i>Technical Background</i> (Updated information) |
| 12 | 01/10/2022 | Revised header (Added Models and Model Year) |
| 11 | 06/25/2020 | Revised <i>Technical Background</i> (Updated information) Revised <i>Service</i> (Updated Figure 2) |

Discontinuation and mixing of Audi-approved engine coolants.

Technical Background

- G11, G12, and G12+ coolants have been replaced by an improved version.
- G12++ coolant (for service available) has been introduced in MY 2005 for all engines.
- G13 has been introduced in MY 2008 as initial fill and service coolant.
- G12evo was introduced in MY19 as initial fill and service coolant.
- Modern combustion engines make higher demands on the coolant. Audi is one of the few manufacturers whose coolant does not require changing. Therefore, the coolant has to be adjusted to the requirements and constantly developed further.



Tip: All model years can use - G12evo part number: Ready to use G -12E-050-1G-DSP **except MY2015 A3 2.0TDI with engine code CRUA, which must still use G13. Only G12evo can be used in the Audi e-tron.**



Technical Service Bulletin

Production Solution

Not applicable.

Service

Identifying and mixing factory fill engine coolants:

1. Based on its color, identify which coolant the vehicle was filled with from the factory (Figure 1).



Tip: Figure 1 is shown for color identification only; coolant packaging may vary.



Figure 1. The color of each type of engine coolant. G11 (green-blue), G12 (red), G12+, G12++, G12evo, and G13 (purple).

2. Using the chart below, determine if the vehicle has the correct coolant (Figure 2). If a vehicle is found to have the incorrect coolant, drain and fill the coolant system using the procedures in ElsaPro.



Technical Service Bulletin

| Can be mixed with: | Green-blue G11 ≥ 1994 | Red G12 ≥ 1996 | Purple G12+ ≥ 2000 | Purple G12++ ≥ 2005 | Purple G13 ≥ 2012 | Purple G12evo ≥ 2018 |
|--------------------|--------------------------|-------------------|-----------------------|------------------------|----------------------|-------------------------|
| G11 | Green | Red | Yellow | Yellow | Yellow | Yellow |
| G12 | Red | Green | Yellow | Yellow | Yellow | Yellow |
| G12+ | Green | Green | Green | Yellow | Yellow | Yellow |
| G12++ | Green | Green | Green | Green | Green | Yellow |
| G13 | Green | Green | Green | Green | Green | Yellow |
| G12evo | Green | Green | Green | Green | Green | Green |

Figure 2. The table identifies which Service coolants (left) can be added to the Factory Filled coolant (top).

| Color | Ratio description |
|----------|---|
| Green = | Can be mixed in any ratio. |
| Yellow = | Mixing is possible but it will cause a reduction in corrosion protection. |
| Red = | Cannot be mixed. |

How to use this table:

1. Check which coolant additive is in the cooling system.
2. Look for the coolant additive in the upper horizontal row.
3. Go down the green column. All coolant types of the green and yellow fields (described in the left vertical column) can be used. **But preferably the coolant marked in a green field should be used.**

Coolants can be mixed, as described in the chart, but it is always best practice to change the coolant due to reduced corrosion protection when coolants are mixed (exception: G12++ and G13 are fully compatible).

Only mix **distilled water** with coolant additives per ElsaPro.


Deionized water must not be used.

Drained coolant must not be reused.



Note:

When the coolant is changed due to a cooling system issue, the cooling system should be drained using the Repair Manual procedures in ElsaPro and refilled with water.



Technical Service Bulletin

Then, run the engine for 15 minutes with the heater on to remove any residual coolant.

The final step is to drain and fill the system to the freeze protection ratio listed in ElsaPro.



Tip: If G11 is mixed with G12+, G12++, G13 or G12evo the coolant becomes brown (this is normal). The G12++ scale should be used when using the refractor T10007B to read the freeze protection for the G12evo coolant.

If it is unclear whether a cooling system is filled with G12, G13 or a mixture of the two, use the G13 scale of the refractors T10007A/B to read the freeze protection.

Cooling system drain and fill due to coolant mixing or incorrect coolant, is not covered by Warranty.

Warranty

This TSB is informational only and not applicable to any Audi Warranty.

Required Parts and Tools

Additional Information

All part and service references provided in this Technical Bulletin (2025303) are subject to change and/or removal. Always check with your Parts Department and/or ETKA for the latest information and parts bulletins. Please check the Repair Manual for fasteners, bolts, nuts, and screws that require replacement during the repair.

©2022 Audi of America, Inc. All rights reserved. The information contained in this document is based on the latest information available at the time of printing and is subject to the copyright and other intellectual property rights of Volkswagen Group of America, Inc., its affiliated companies and its licensors. All rights are reserved to make changes at any time without notice. No part of this document may be reproduced, stored in a retrieval system, or transmitted in any form or by any means, electronic, mechanical, photocopying, recording, or otherwise, nor may these materials be modified or reposted to other sites, without the prior expressed written permission of the publisher.